

MV-VC4719-350RT

Vision Processor



Introduction

MV-VC4719-350RT Vision Processor adopts Intel® i7 CPU and memory of 8 GB. It supports 8 I/O inputs and outputs, and integrates 4 light interfaces with constant voltage. The vision controller has multiple GigE and USB3.0 interfaces, and it can connect with CameraLink and CoaXPress frame grabber via expansion slot.

Supports extensible POE NIC

Built-in dual USB3.0 dongle slots

Adopts Intel® GigE interface for image transmission

Key Feature

Onboard Intel® i7 CPU, and supports 1660 GPU

Adopts multiple expansion slots to connect with different frame grabbers


Integrates 4 light interfaces with constant voltage

Supports 16 GPIO inputs and outputs and NPN/PNP switch

Applicable Industry

Computer, communication and consumer electronic, food and pharmaceuticals, transportation, etc.

Dimension



Specification

Model	MV-VC4719-350RT
Performance	
CPU	Intel®Core i7 max turbo boost 4.0GHz
Memory	8 GB
Storage	128 GB SSD, 2TB SATA HDD *
GPU	Intel® HD Graphics 530
External interface	
Video output	HDMI interface x 1, VGA interface x 1; Supports independent display, max. resolution: 4096 × 2304 @24Hz
GPIO	Opto-isolated input x 8, opto-isolated output x 8 (supports NPN/PNP switch)
Light interface	Light interfaces with 24 VAC constant voltage x 4, controllable brightness; Max. current 2.5 A for single light interface; Max. power consumption: 70 W; Supports external trigger strobe and solid mode switch
Network interface	Intel® GigE interfaces x 2, built-in 4 GigE Interfaces and POE NIC *
USB interface	USB3.0 x 8, built-in USB3.0 x 2
Serial port	RS-232 x 2
Extension interface	PCIe x16 (x 1) or PCIe x8 (x 2), PCI (x 1), PCIe x4 (x 1)
Electrical features	
Power supply	100 VAC to 240 VAC
Power consumption	≤350W *
Structure	
Dimension	306 mm x 180 mm x 287 mm (12.0" x 7.1" x 11.3")
Weight	Approx. 7.5 kg (16.5 lb.)
Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Humidity	20% to 95% RH, without condensation
General	
Operating system	Windows 10 included *
Certifications	CCC, CE, FCC

*1: MV-VC4719-350RT included 128 GB SSD + 2 TB HDD

*2: MV-VC4719-350RT installed Window 10

*3: MV-VC4719-350RT have 4 port GigE PoE to connect camera.

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.

No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.

en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.

MV-VC4719-128G20

Vision Processor



Introduction

MV-VC4719-128G20 Vision Processor adopts Intel® i7 CPU and memory of 8 GB. It supports 8 I/O inputs and outputs, and integrates 4 light interfaces with constant voltage. The vision troller has multiple GigE and USB3.0 interfaces, and it can connect with CameraLink and CoaXPRESS frame grabber via expansion slot.

Supports extensible POE NIC
Built-in dual USB3.0 dongle slots
Adopts Intel® GigE interface for image transmission

Key Feature

Onboard Intel® i7 CPU, and supports 1660 GPU

Adopts multiple expansion slots to connect with different frame grabbers


Integrates 4 light interfaces with constant voltage

Supports 16 GPIO inputs and outputs and NPN/PNP switch

Applicable Industry

Computer, communication and consumer electronic, food and pharmaceuticals, transportation, etc.

Dimension



Specification

Model	MV-VC4719-128G20
Performance	
CPU	Intel® Core i7
Memory	8 GB
Storage	128 GB SSD
GPU	Intel® HD Graphics 530
External interface	
Video output	HDMI interface x 1, VGA interface x 1; Supports independent display, max. resolution: 4096 × 2304 @24Hz
GPIO	Opto-isolated input x 8, opto-isolated output x 8 (supports NPN/PNP switch)
Light interface	Light interfaces with 24 VAC constant voltage x 4, controllable brightness; Max. current 2.5 A for single light interface; Max. power consumption: 70 W; Supports external trigger strobe and solid mode switch
Network Interface	Intel® GigE interfaces x 2
USB interface	USB3.0 x 8, built-in USB3.0 x 2
Serial port	RS-232 x 2
Extension interface	PCIe x16 (x 1) or PCIe x8 (x 2), PCI (x 1), PCIe x4 (x 1)
Electrical features	
Power supply	100 VAC to 240 VAC
Power consumption	≤350W
Structure	
Dimension	306 mm x 180 mm x 287 mm (12.0" x 7.1" x 11.3")
Weight	Approx. 7.5 kg (16.5 lb.)
Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Humidity	20% to 95% RH, without condensation
General	
Operating system	Support Windows 10 (purchased separately)
Certifications	CCC, CE, FCC

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.

MV-VC4710-128G20

Vision Processor



Introduction

MV-VC4710-128G20 Vision Processor adopts Intel® i7 CPU and memory of 8 GB. It supports 8 I/O inputs and outputs, and integrates 4 light interfaces with constant voltage. The vision controller has multiple GigE and USB3.0 interfaces, and it can connect with CameraLink and CoaXPress frame grabber via expansion slot.

Supports extensible POE NIC

Built-in dual USB3.0 dongle slots

Adopts Intel® GigE interface for image transmission

Key Feature

Onboard Intel® i7 CPU, and supports 1660 GPU

Adopts multiple expansion slots to connect with different frame grabbers


Integrates 4 light interfaces with constant voltage

Supports 16 GPIO inputs and outputs and NPN/PNP switch

Applicable Industry

Computer, communication and consumer electronic, food and pharmaceuticals, transportation, etc.

Dimension



Specification

Model	MV-VC4710-128G20
Performance	
CPU	Intel® Core i7
Memory	8 GB
Storage	128 GB SSD
GPU	Intel® HD Graphics 530
External interface	
Video output	HDMI interface x 1, VGA interface x 1; Supports independent display, max. resolution: 4096 × 2304 @24Hz
GPIO	Opto-isolated input x 8, opto-isolated output x 8 (supports NPN/PNP switch)
Light interface	Light interfaces with 24 VAC constant voltage x 4, controllable brightness; Max. current 2.5 A for single light interface; Max. power consumption: 70 W; Supports external trigger strobe and solid mode switch
Network interface	Intel® GigE interfaces x 2
USB interface	USB3.0 x 8, built-in USB3.0 x 2
Serial port	RS-232 x 2
Extension interface	PCIe x16 (x 1) or PCIe x8 (x 2), PCI (x 1), PCIe x4 (x 1)
Electrical features	
Power supply	100 VAC to 240 VAC
Power consumption	≤250W
Structure	
Dimension	306 mm x 180 mm x 287 mm (12.0" x 7.1" x 11.3")
Weight	Approx. 7.5 kg (16.5 lb.)
Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Humidity	20% to 95% RH, without condensation
General	
Operating system	Support Windows 7/10 (purchased separately)
Certifications	CCC, CE, FCC

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.

MV-VC4710-128G60

Vision Processor



Introduction

MV-VC4710-128G60 Vision Processor adopts Intel® i7 CPU and memory of 8 GB. It supports 8 I/O inputs and outputs, and integrates 4 light interfaces with constant voltage. The vision controller has multiple GigE and USB3.0 interfaces, and it can connect with CameraLink and CoaXPress frame grabber via expansion slot.

Supports extensible POE NIC

Built-in dual USB3.0 dongle slots

Adopts Intel® GigE interface for image transmission

Key Feature

Onboard Intel® i7 CPU, and supports 1660 GPU

Adopts multiple expansion slots to connect with different frame grabbers


Integrates 4 light interfaces with constant voltage

Supports 16 GPIO inputs and outputs and NPN/PNP switch

Applicable Industry

Computer, communication and consumer electronic, food and pharmaceuticals, transportation, etc.

Dimension



Specification

Model	MV-VC4710-128G60
Performance	
CPU	Intel® Core i7
Memory	8 GB
Storage	128 GB SSD
GPU	Intel® HD Graphics 530
External interface	
Video output	HDMI interface x 1, VGA interface x 1; Supports independent display, max. resolution: 4096 × 2304 @24Hz
GPIO	Opto-isolated input x 8, opto-isolated output x 8 (supports NPN/PNP switch)
Light interface	Light interfaces with 24 VAC constant voltage x 4, controllable brightness; Max. current 2.5 A for single light interface; Max. power consumption: 70 W; Supports external trigger strobe and solid mode switch
Network interface	Intel® GigE interfaces x 2, built-in 4 GigE Interfaces and POE NIC
USB interface	USB3.0 x 8, built-in USB3.0 x 2
Serial port	RS-232 x 2
Extension interface	PCIe x16 (x 1) or PCIe x8 (x 2), PCI (x 1), PCIe x4 (x 1)
Electrical features	
Power supply	100 VAC to 240 VAC
Power consumption	≤250W
Structure	
Dimension	306 mm x 180 mm x 287 mm (12.0" x 7.1" x 11.3")
Weight	Approx. 7.5 kg (16.5 lb.)
Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Humidity	20% to 95% RH, without condensation
General	
Operating system	Support Windows 7/10 (purchased separately)
Certifications	CCC, CE, FCC

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.